

## PRODUCT LIST

### IDENTIFICATION



**PC**  
PC969

**NAME**  
MONA SMALL WALL D340 H435

**TYPE**  
WALL LAMP


**COLLECTION**  
MONA SMALL

**LINE**  
EXCLUSIVE LINE

**DESIGNED BY**  
LUCIE KOLDOVÁ

**DIMENSIONS (MM)**  
340 x 435 x - x -

**PC969**



### CHARACTERISTIC

#### FEATURES

THE MONA COLLECTION IS BASED ON THE CONCEPT OF PENETRATING FORMS. THE LIGHT SOURCE BOLDLY TRAVERSES THE AMPLE VOLUME OF SMOOTH HANDBLOWN GLASS TO REVEAL THE THRILLING TENSION INHERENT IN THE DESIGN. THE COLLECTION'S ESSENCE, HOWEVER, LIES IN ITS UNCONVENTIONAL CONSTRUCTION AND REFINED COMBINATION OF MATERIALS. IT ALSO BOASTS DIMMABLE TUBULAR LED LIGHT SOURCES, DEVELOPED BY BROKIS, EACH WITH A DIFFERENT COLOUR TEMPERATURE. THE MONA SMALL COLLECTION INCLUDES WALL AND TABLES LIGHTS OF THE SMALLEST PROPORTIONS COMPARED WITH THE OTHER MONA COLLECTIONS.

#### TECHNOLOGY

COMBINED CRAFTSMANSHIP / HAND-BLOWN GLASS IN COMBINATION WITH OAK AND METAL BODY. THE CRAFTSMANSHIP APPLIED IN PRODUCTION FOLLOWS IN THE CENTURIES-OLD TRADITION AND EXPERIENCE OF MASTER GLASSMAKERS. THE PRECISION CRAFTING OF HAND-BLOWN GLASS INSTILLS DISTINCTIVE, ENDURING CHARACTER AND OUTSTANDING QUALITY IN ALL BROKIS PRODUCTS. THE GLASS SHADES ARE FORMED FROM MULTIPLE LAYERS OF MOLTEN GLASS, EACH OF WHICH IS SCRUTINIZED BY THE MASTER GLASSMAKER PRIOR TO BEING BLOWN INTO THE MOLD. UP TO 70% OF THE RESULTING QUALITY IS ACHIEVED IN THIS STAGE OF PRODUCTION.



## PRODUCT LIST

### PRODUCT CLASSIFICATION

MONA SMALL	WALL		PC969
GLASS COLOUR	BAS	BLACK - TRANSPARENT GLASS	CGC602 •
GLASS COLOUR	BAS	VIOLET - TRANSPARENT GLASS	CGC554 •
GLASS COLOUR	BAS	OPALINE - TRANSPARENT GLASS	CGC38 •
GLASS COLOUR	BAS	SMOKE GREY - TRANSPARENT GLASS	CGC516 •
GLASS COLOUR	BAS	TRANSPARENT GLASS	CGC23 •
GLASS SURFACE	ALL	GLOSSY SURFACE	CGSU66
SURFACE FINISH	BAS	LAMP BODY - WHITE	CCS732 •
SURFACE FINISH	BAS	LAMP BODY - BLACK	CCS727 •
BULBS	BAS	24V, LED, 2,5W, 2700K, 141LM, RA80+, DIM	CEB1986
BULBS	BAS	24V, LED, 2,5W, 4000K, 173LM, RA80+, DIM	CEB1987
BULBS	BAS	24V, LED, 2,5W, 5000K, 184LM, RA80+, DIM	CEB1988
DIMMABLE VERSION	BAS	INTEGRATED DIMMER ON THE BODY OF THE LUMINAIRE	CEDV1463
SCREW CAP	ALL	NON-USER REPLACEABLE LIGHT SOURCE	CESC2488
POWER VOLTAGE (VAC)	ALL	90-264VAC	PV2526
STANDARTS	ALL	CE	CEC160
STANDARTS	ALL	EN 60598-1 ED.6:2015	CEC569
STANDARTS	ALL	EN 60598-2-1:1997	CEC568
STANDARTS	ALL	IEC 60598-1:2014	CEC2471
STANDARTS	ALL	IEC 60598-2-1:1979+ A1:1987	CEC2472

